

ADECO ULTRA SYNTH ULTIMATE SAE 0W-30

Product Description:

ADECO ULTRA SYNTH ULTIMATE SAE 0W-30 is a fully synthetic ultra-high performance "Mid SAPS" engine oil, designed to protect the latest generation of engines. It features advanced technologies to reduce exhaust emissions.

Purpose:

ADECO ULTRA SYNTH ULTIMATE SAE 0W-30 is recommended for the lubrication of passenger vehicles with gasoline and diesel engines.

Well adapted for use in the latest engines of the PSA group, especially those with the e-HDi label (Eng. ECO High-pressure direct injection) that use Stop & Start technologies and hybrid engines that require new generation engine oils.

Provides superior protection for LSPI engines and all associated DPF and GPF exhaust gas treatment systems. Suitable for use in hybrid vehicles.

The Main Advantages

- Maximum engine protection at high loads and high temperatures;
- Excellent detergent-dispersing properties of the oil;
- Facilitates cold engine start, even at very low temperatures;
- Excellent tribological characteristics reduce the wear of engine parts;
- Produžen interval zamene ulja i značajna ušteda goriva;
- Reduction of particle emissions, especially NOx, HC and CO).

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15°C, g/cm ³	0,844	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	45-60	ASTM D 445
Kinematic Viscosity at 100°C, mm ² /s	9.3-12.5	ASTM D 445
Viscosity index, min	170	ASTM D 2270
Flash Point, COC, °C, min	230	ASTM D 93
Pour point, °C, max	-45	ASTM D 97
Total base number, TBN, mgKOH/g, min	6	ASTM D 2896
Sulfated ash,% m/m, max	0.8	ASTM D 874

Meet Specifications:

ACEA C2, API SP